



PRODUCT INFO:

- **Type of frame:** carton, plastic, metal
- **Type of medium:** synthetic material or fibreglass
- **Depth of frame:** according the material type
Carton frame: 20 – 100 mm
Plastic frame: 20, 25, 48, 96, 150 mm
Metal frame: 20 – 150 mm
- **Media color:** according the material type
- **Operating temperature:** up to 60 °C
- **Recommended final pressure drop:** 200 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Warranty:** valid for the entire service life of the filter

GENERAL DESCRIPTION:

- Used as pre-filters or main filters in ceiling-mounted or air intake units.
- Custom dimensions available upon request.



VLAFIR

Filtration class EN 779	EN ISO 16890	Product	Width (mm)	Height (mm)	Depth (mm)	Filter surface (m ²)	Airflow (m ³ /h)	Initial pressure drop (Pa)	Recom. final diff. pressure (Pa)
G2	ISO Coarse 40 %	592x592x10	592	592	10	0,4	3400	55	200
G3	ISO Coarse 50 %	592x592x10	592	592	10	0,4	3400	70	200
G4	ISO Coarse 60 %	592x592x10	592	592	10	0,4	3400	90	200
M5	ISO ePM10 50 %	592x592x10	592	592	10	0,4	3400	150	200

