



PRODUCT INFO:

- **Type of frame:** plastic
- **Type of medium:** highly durable synthetic material with a multilayer structure
- **Media color:** white
- **Operating temperature:** up to 70 °C
- **Recommended final pressure drop:** 200 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Packaging:** packed in cartons; the label indicates the type of filter, size, efficiency according to EN ISO 16890, or filtration class and manufacturer
- **Warranty:** valid for the entire service life of the filter

GENERAL DESCRIPTION:

- The robust, self-supporting construction.
- For applications that require long service life and high operational reliability (offices, laboratories, data centers), as well as in industrial sectors with demanding operating conditions (paint lines, automotive, pharmaceutical production, and the food industry).



HIGH STRENGTH POCKET FILTER ePM2,5 70 % (F7)

Product	Width (mm)	Height (mm)	Depth (mm)	Amount of pocket	Filter surface (m ²)	Airflow (m ³ /h)	Initial pressure drop (Pa)	Recom. final diff. pressure (Pa)
592×592×600	592	592	600	8	5,7	3400	115	300
490×592×600	490	592	600	6	4,3	2600	115	300
287×592×600	287	592	600	4	2,8	1700	115	300