



## PRODUCT INFO:

- **Type of frame:** plastic
- **Type of medium:** highly durable synthetic material with a multilayer structure
- **Media color:** white
- **Operating temperature:** up to 70 °C
- **Recommended final pressure drop:** 200 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Packaging:** packed in cartons; the label indicates the type of filter, size, efficiency according to EN ISO 16890, or filtration class and manufacturer
- **Warranty:** valid for the entire service life of the filter

## GENERAL DESCRIPTION:

- The robust, self-supporting construction.
- For applications that require long service life and high operational reliability (offices, laboratories, data centers), as well as in industrial sectors with demanding operating conditions (paint lines, automotive, pharmaceutical production, and the food industry).



## HIGH STRENGTH POCKET FILTER ISO COARSE 75 % (G4)

| Product     | Width (mm) | Height (mm) | Depth (mm) | Amount of pocket | Filter surface (m <sup>2</sup> ) | Airflow (m <sup>3</sup> /h) | Initial pressure drop (Pa) | Recom. final diff. pressure (Pa) |
|-------------|------------|-------------|------------|------------------|----------------------------------|-----------------------------|----------------------------|----------------------------------|
| 592×592×600 | 592        | 592         | 600        | 7                | 5                                | 3400                        | 35                         | 200                              |
| 490×592×600 | 490        | 592         | 600        | 6                | 4,3                              | 2900                        | 35                         | 200                              |
| 287×592×600 | 287        | 592         | 600        | 4                | 2,8                              | 1900                        | 35                         | 200                              |