



PRODUCT INFO:

- **Type of frame:** MDF, metal, plastic, AL sheet
- **Type of medium:** fiber glass
- **Media color:** white
- **Available versions:** minipleat (pleat height 20 – 200 mm)
Al separation (depth of frame 150 - 292 mm)
- **Type of seal:** flat, half-round, double-lip
- **Operating temperature:** max. 70 °C
- **Recommended final pressure drop:** 300 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Warranty:** valid for the entire service life of the filter

GENERAL DESCRIPTION:

- **Application:** metrology and calibration laboratories, optical and electronics industries, biological laboratories, and ventilation systems in nuclear power plants.



PANEL FILTERS MINIPLEAT FIBER GLASS

Filtration class EN 779	Filtration class EN ISO 16890	Product	Width (mm)	Height (mm)	Depth (mm)	Airflow (m³/h)	Initial pressure drop (Pa)	Recom. final pressure drop (Pa)
M6	ePM10 75 %	592x592x48	592	592	48	1700	75	300
M6	ePM10 75 %	592x287x48	592	287	48	1000	90	300
M6	ePM10 75 %	592x592x96	592	592	96	2500	60	300
M6	ePM10 75 %	592x287x96	592	287	96	1200	70	300
F7	ePM1 60 %	592x592x48	592	592	48	1700	100	300
F7	ePM1 60 %	592x287x48	592	287	48	1000	130	300
F7	ePM1 60 %	592x592x96	592	592	96	2500	90	300
F7	ePM1 60 %	592x287x96	592	287	96	1200	100	300
F9	ePM1 85 %	592x592x48	592	592	48	1700	180	300
F9	ePM1 85 %	592x287x48	592	287	48	1000	220	300
F9	ePM1 85 %	592x592x96	592	592	96	2500	150	300
F9	ePM1 85 %	592x287x96	592	287	96	1200	170	300