



PRODUCT INFO:

- **Type of frame:** metal
- **Type of medium:** fiber glass
- **Media color:** orange
- **Operating temperature:** up to 70 °C
- **Recommended final pressure drop:** 200 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Packaging:** packed in cartons; the label indicates the type of filter, size, efficiency according to EN ISO 16890, or filtration class and manufacturer
- **Warranty:** valid for the entire service life of the filter

GENERAL DESCRIPTION:

- Suitable for all types of air handling units.
- Used as a secondary or final stage of filtration for capturing fine dust particles.



FIBER GLASS POCKET FILTER ePM10 60 % (M5)

Product	Width (mm)	Height (mm)	Depth (mm)	Amount of pocket	Filter surface (m ²)	Airflow (m ³ /h)	Initial pressure drop (Pa)	Recom. final diff. pressure (Pa)
592x592x600	592	592	600	10	7,5	3400	33	200
490x592x600	490	592	600	8	6	2800	33	200
592x490x600	592	490	600	10	6	2800	33	200
287x592x600	287	592	600	5	3,7	1700	33	200
592x287x600	592	287	600	10	3,8	1700	33	200
287x287x600	287	287	600	5	1,9	850	33	200