



### PRODUCT INFO:

- **Type of frame:** metal
- **Type of medium:** fiber glass
- **Media color:** green
- **Operating temperature:** up to 70 °C
- **Recommended final pressure drop:** 200 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Packaging:** packed in cartons; the label indicates the type of filter, size, efficiency according to EN ISO 16890, or filtration class and manufacturer
- **Warranty:** valid for the entire service life of the filter

### GENERAL DESCRIPTION:

- Suitable for all types of air handling units.
- Used as a secondary or final stage of filtration for capturing fine dust particles.



### FIBER GLASS POCKET FILTER ePM2,5 50 % (M6)

Product	Width (mm)	Height (mm)	Depth (mm)	Amount of pocket	Filter surface (m <sup>2</sup> )	Airflow (m <sup>3</sup> /h)	Initial pressure drop (Pa)	Recom. final diff. pressure (Pa)
592x592x600	592	592	600	10	7,5	3400	69	200
490x592x600	490	592	600	8	6	2800	69	200
592x490x600	592	490	600	10	6	2800	69	200
287x592x600	287	592	600	5	3,7	1700	69	200
592x287x600	592	287	600	10	3,8	1700	69	200
287x287x600	287	287	600	5	1,9	850	69	200