



PRODUCT INFO:

- **Type of frame:** plastic, metal
- **Type of medium:** synthetic material
- **Media color:** pink
- **Operating temperature:** up to 80 °C
- **Recommended final pressure drop:** 300 Pa
- **Disposal:** can be disposed of in incinerators or municipal waste landfill
- **Packaging:** packed in cartons; the label indicates the type of filter, size, efficiency according to EN ISO 16890, or filtration class and manufacturer
- **Warranty:** valid for the entire service life of the filter

GENERAL DESCRIPTION:

- Suitable for all types of air handling units.
- **Application according to filtration class:** used as a secondary or final filtration stage for separating fine dust particles in telecommunications centers, food processing facilities, hospitals, and similar environments.
- Custom dimensions available upon request.



POCKET FILTER ePM2,5 65 % (F7)

Product	Width (mm)	Height (mm)	Depth (mm)	Amount of pocket	Filter surface (m ²)	Airflow (m ³ /h)	Initial pressure drop (Pa)	Recom. final diff. pressure (Pa)
592×592×600	592	592	600	8	6	3400	107	300
490×592×600	490	592	600	6	4,4	2800	107	300
592×490×600	592	490	600	8	4,5	2800	107	300
287×592×600	287	592	600	4	2,9	1700	107	300
592×287×600	592	287	600	6	2,4	1700	107	300
287×287×600	287	287	600	3	1,5	900	107	300